

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
4 January 2001 (04.01.2001)

PCT

(10) International Publication Number
WO 01/00395 A1

(51) International Patent Classification⁷: B29D 30/06,
B29C 43/10

(74) Agent: TANSINI, Elio, Fabrizio: Bugnion S.p.A., Viale
Lancetti, 17, I-20158 Milano (IT).

(21) International Application Number: PCT/EP00/05389

(22) International Filing Date: 13 June 2000 (13.06.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
99830405.9 25 June 1999 (25.06.1999) EP
60/147.027 3 August 1999 (03.08.1999) US

(71) Applicant (for all designated States except US): PIRELLI
PNEUMATICI S.P.A. [IT/IT]; Viale Sarca, 222, I-20126
Milano (IT).

(72) Inventor; and

(75) Inventor/Applicant (for US only): CARETTA, Renato
[IT/IT]; Viale dei Tigli, 16, I-21013 Gallarate (IT).

(81) Designated States (national): AE, AL, AM, AT, AU, AZ,
BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK,
DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL,
IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU,
LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT,
RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA,
UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— With international search report.

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR MOULDING AND CURING TYRES FOR VEHICLE WHEELS



(57) Abstract: A green tyre (7) manufactured on a toroidal support (10) is closed in a vulcanization mould (2). Side portions (8) of the tyre are sandwiched between mould cheeks (4a, 4b) and the toroidal support (10). Steam or another fluid under pressure is fed to a diffusion interspace (19) formed, due to tyre expansion, between the inner surface of the tyre (7) and the outer surface (10a) of the toroidal support (10). A pre-cured liner is previously applied to the inner surface of the tyre (7), to prevent diffusion of water particles in the raw elastomer material.

WO 01/00395 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.